

# **BLANK PAGE**



**IS:4210-1967** 

(Reaffirmed 1983)

# Indian Standard

REAFFIRMED

### SPECIFICATION FOR STRIP FEELER GAUGES FOR ELECTRICAL PURPOSES

2008

Second Reprint DECEMBER 1988

(Incorporating Amendment No. 1)

UDC 531.718.41:621.3

© Copyright 1979

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

## Indian Standard SPECIFICATION FOR STRIP FEELER GAUGES FOR ELECTRICAL PURPOSES

#### Engineering Metrology Sectional Committee, EDC 43

Chairman

Representing

DR K. N. MATHUR

In personal capacity (National Physical Laboratory, New Delhi )

#### Members

COL V. P. BAJAJ

Ministry of Defence (DGI)

SHRI S. N. ADHIKARI ( Alternate ) SHRI R. S. BIR

Hindustan Machine Tools Ltd. Bangalore

SHRI M. RANGASHAI ( Alternate

Motor Industries Co Ltd, Bangalore

SHRI H. BULGRIN SHRI P. S. SANKRALINGAM ( Alternate)

SHRI S. CHAMARAJAN SHRI A. D. GHATE

Jyoti Ltd, Baroda Poona Gauge and Tool Co, Poona National Test House, Calcutta

SHRI A. GHOSH SHRI S. P. GOYAL SHRI I. B. GURA

Indian Engineering Association, Calcutta Jay Engineering Works Ltd, Calcutta

SHRI B. N. GUPTA

Engineering Association of India, Calcutta Heavy Machine Building Plant, Heavy Engineering

SHRI P. N. GUPTA

Corporation Ltd, Ranchi

SRRI M. P. KUMARASWAMY

Central Mechanical Engineering Research Institute (CSIR), Durgapur

SHRI R. V. RAMACHANDRAN ( Alternate ) SHRI PREM PRAKASH

National Physical Laboratory (CSIR), New Delhi

SHRI P. C. JAIN ( Alternate ) SHRI D. D. PURI

Central Scientific Instruments Organization (CSIR). New Delhi

SRRI K. RAGHUNATHAN Dr A. RAMACHANDRAN

Ministry of Railways

SHRI R. KRISHNAN ( Alternate )

Indian Institute of Science, Bangalore

SHRI S. RAMACHANDRAN SHRI N. RAMAJAYAM

Mahindra & Mahindra Ltd, Bombay Ex-Cell-O India Ltd, Bombay

SRRI V. B. SALUNKE SERI W. H. SIDDIQI

The Accurate Engineering Co (P) Ltd, Poona

The Praga Tools Ltd, Secunderabad

SHRI D. R. NARAYANA ( Alternate )

(Continued on page 2)

#### 18: 4210 - 1967

#### (Continued from page 1)

Members

Representing

SHRI C. R. SONALKAR

Indian Machine Tool Manufacturers' Association, Bombay

SHRI M. V. PATANKAR. Director ( Mech Engg ) Director General, ISI (Ex-officio Member)

Secretary

SHRI S. CHANDBASEKHARAN Deputy Director (Mech Engg), ISI

Gauges Subcommittee, EDC 43:3

Convener

SHRI PREM PRAKASH

National Physical Laboratory (CSIR), New Delhi

Members

SHRI MOHINDER NATH ( Alternate to

Shri Prem Prakash)

SHRI H. BULGRIN Motor Industries Co Ltd. Bangalore

SERI P. S. SANKRALINGAM ( Alternate )

SHRI A. D. GHATE Poona Gauge and Tool Co, Poona

SRRI S. C. KHAN Indian Engineering Association, Calcutta

SHRI B. SEN ( Alternate )

SHRI K. KUMAR Engineering Association of India, Calcutta

SHRI S. M. KALE ( Alternate )

SHRI M. RANGASHAI Hindustan Machine Tools Ltd, Bangalore

SHRI S. KANNAN ( Alternate ) SARI M. H. RAO

The Praga Tools Ltd, Secunderabad SHRI V. B. SALUNKE The Accurate Engineering Co (P) Ltd, Poona

Central Mechanical Engineering Research Institute DR M. M. SURI

(CSIR), Durgapur Ministry of Defence (DGI)

COL S. C. TRIGUNAYAT

# Indian Standard SPECIFICATION FOR STRIP FEELER GAUGES FOR ELECTRICAL PURPOSES

#### O. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 20 July 1967, after the draft finalized by the Engineering Metrology Sectional Committee had been approved by the Mechanical Engineering Division Council.
- **0.2** This standard is expected to meet the requirements of strip feeler gauges used in electrical machinery for the measurement of air gap. Feeler gauges are covered in IS: 3179-1976.
- 0.3 This standard does not cover the requirements of feeler gauges used for inspecting air gap in small, low torque fractional horsepower motors incorporating permanent magnet rotors.
- 0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS: 2-1960†. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

#### 1. SCOPE

1.1 This specification applies to strip feeler gauges comprising a series of gauging blades of graded thicknesses from 0·1 mm to 1·0 mm and 1·0 mm to 2·0 mm.

#### 2. MATERIAL

2.1 The blades shall be made of heat treated bright polished tool steel having a tensile strength not less than 170 kgf/mm<sup>2</sup> for thickness up to 0.5 mm and not less than 70 kgf/mm<sup>2</sup> for thickness above 0.5 mm.

<sup>\*</sup>Specification for feeler gauges (0.03 to 1 mm) (first revision).

<sup>†</sup>Rules for rounding off numerical values ( revised ).

#### IS: 4210 - 1967

#### 3. DIMENSIONS AND TOLERANCES

3.1 Thickness — The thicknesses of the blades in millimetres shall be the following:

- 3.2 Length The length of the blades shall be 500 and 1000 mm.
- 3.3 Width The width of the blades shall be 12 mm.
- 3.4 Thickness Variation The thickness taken at different points along the length of blade should be within the variation  $\pm 0.005$  mm on the nominal thickness. The maximum variation in the thickness of a blade shall not exceed 0.006 mm.

#### 4. GENERAL REQUIREMENTS

- 4.1 Hardness The plates shall be hardened and tempered to not sess than 540 HV (see IS: 1501-1968\*).
- 4.2 When the two ends of the blades are brought together the blade shall not break. Also when the two ends are released after being brought together the blade shall return to its original straight position without any residual bend. Further when the blade is inserted in an air gap to measure the gap it should take any bends in the gap without breakage.
- 4.3 The blades shall be provided with a 4 mm hole at one end. Set of blades shall be supplied suitably assembled.
- 4.4 The outer ends of the blades shall be semicircular and the blades, throughout their length, shall be free from sharp edges.

#### 5. MARKING

- 5.1 Each blade shall be legibly and permanently marked with its nominal thickness at a distance of 90 mm (approximate) from the drilled hole end.
- 5.1.1 The strip feeler gauges may also be marked with the ISI Certification Mark.

Note — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

<sup>\*</sup>Method for Vickers hardness test for steel (first revision).

#### 6. PACKING

- 6.1 As a protection against climatic conditions, the blades shall be coated with a suitable anti-corrosive preparation. To prevent any damage due to bending in transport, it is recommended that these strip feeler gauges should be supplied in a stiff leather cover or of suitable stiff material.
- 6.2 Recommended sets of strip feeler gauges are given below:

Set No.	Number of Blades in a Set	Thickness of Blades mm	
1	10	{ 0·1, 0·2, 0·3, 0·4, 0·5, 0·6, 0·7, 0·8, 0·9, 1·0	
2	11	{ 1·0, 1·1, 1·2, 1·3, 1·4, 1·5 1·6, 1·7, 1·8, 1·9, 2·0	

#### BUREAU OF INDIAN STANDARDS

Headquarters :	
Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELI	HI 110002
•	: Manaksanstha to all Offices)
Regional Offices :	Telephone
*Western ; Manakalaya, E9 MIDC, Marol, Andheri ( Eas BOMBAY.40003	it), 6 32 92 95
Sastern: 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola, CALCUTTA 700054	36 24 99
Northern: SCO 445-446, Sector 35-C CHANDIGARH 160036	{2 18 43 3 16 41
Southern: C. I. T. Campus, MADRAS 600113	\[ \begin{pmatrix} 41 & 24 & 42 \\ 41 & 25 & 19 \\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Branch Offices :	<b>L41 29 16</b>
Pushpak,' Nurmohamed Shaikh Marg, Khanpur, AHMADABAD 380001	<b>{2 63 48 2 63 49</b>
'F' Block, Unity Bldg, Narasimharaja Square, BANGALORE 560002	22 48 05
Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. N BHOPAL 462003	
Plot No. 82/83, Lewis oad, BHUBANESHWAR 75100	5 36 27
53/5 Ward No. 29, R. G. Barua Road, 5th Byelane, GUWAHATI 781003	****
5-8-56C L. N. Gupta Marg, (Nampaily Station Road), HYDERABAD 500001	22 10 83
R14 Yudhister Marg, C Scheme, JAIPUR 302005	\[ \{ 6 34 71 \\ 6 98 32 \]
117/418B Sarvodaya Nagar, KANPUR 208005	{21 68 76 21 82 92
Patliputra Industrial Estate, PATNA 800013	6 23 05
Hantex Bldg ( 2nd Floor ), Rly Station Road, TRIVANDRUM 695001	52 27
Inspection Office ( With Sale Point ):	
Institution of Engineers ( India ) Building, 1332 Shivaji PUNE 410005	Nagar, 5 24 35
*Sales Office in Bombay is at Novelty Chambers, Grant Ro Bombay 400007	ad, 89 65 28
†Sales Office in Calcutta is at 5 Chowringhee Approach, P. O. I Street, Calcutta 700072	Princep 27 88 00